

USB3.1 C female to female keystone coupler

A USB C (generation 2) keystone coupler designed to transmit power, data and audio at speeds up to 10Gbps.

Its standardised dimensions allow it to be used for easy snap-in mounting into keystone patch panels, wall plates, adaptors, or surface mount boxes.



Front View



Rear View

FEATURES:

- Single wired connection transmits at twice the speed as USB 3.0 connectors (10Gbps vs 5Gbps)
- Backwards compatible with USB3.0 (first generation) versions of USB C
- Standard profile keystones offered in black and white
- Compact profile makes it suitable for use in faceplates, eg by use of Euro or 6C faceplate adaptors
- Current rating: 5A

SPECIFICATION:

- Compatible with USB Revision 3.1 / 3.0 / 2.0
- Transfer rates up to 10Gbps
- Capable of handling up to 100W
- Current Rating: 5A max.
- Dielectric Withstanding Voltage: 100V AC 10ms
- Insulation Resistance: 100M ohm min.

MATERIALS:

- Colour – Black or White
- Connection – USB3.1 type C 2nd Generation female to female connector
- Housing - ABS+PV+UV FR | Fire retardant ABS plastic
- Shell - Brass contacts with flash gold plating
- Weight: 7g
- Dimensions: 29.40 mm x 17 mm x 21.74 mm

ADDITIONAL NOTES:

• **The transmission of signal or current is entirely dependent on the wiring of cables and equipment connected. If polarity sensitive equipment is connected, users might need to rotate connectors 180 degrees.**

- Commodity Code: 85444920

Part No.	Description	Colour
11-6047-B	Black USB-C 3.1 Keystone (f-f coupler)	Black
11-6047-W	White USB-C 3.1 Keystone (f-f coupler)	White